



Indoor / Outdoor Lockable Distribution Box
IP65 Rated Supports up to 12 Fibres

V.3.0



Fibre cable and patchcords available separately



Indoor / Outdoor Lockable Distribution Box

IP65 Rated Supports up to 12 Fibres

Description

This Lockable IP65 distribution box offers the ability to terminate 12 fibres housed in a strong robust ABS enclosure for indoor and outdoor applications.

With the ability to use a full array of adapter types offering a flexible solution to the end user, enabling them to incorporate a multi functional enclosure which allows easy access during installation or re-work with no disturbance of the existing cable or fibres.

In addition to the array of adaptors the enclosure also offers up to 12 exit points for patching cables and 1 standard cable entry points for loose tube, tight buffer, pre-terminated and steel tape armoured cable.

Each enclosure has integrated strength member tie positions and bend radius protection with the addition of a removable front door allowing for quick and easy installation.

Features/Benefits

- ▶ Up to 12 fibres
- ▶ Removable splice tray for easy installation
- ▶ Multiple adapter options available
- ▶ 6 adapter positions
- ▶ IP 65
- ▶ Accepts loose tube, distribution and pre terminated cables
- ▶ Integrated bend radius protection
- ▶ Sealing glands for up to 12 cables
- ▶ Lockable door
- ▶ Removable door for ease of installation
- ▶ ROHS, REACH SvHC
- ▶ Supplied with 12 heatshrink splice protectors
- ▶ Supplied with transit tubing
- ▶ Supplied with wall fixings and tie wraps

Applications

- ▶ Data centres, premise installations, telecommunication networks
- ▶ Ethernet, Fibre Channel, ATM, LAN, MAN and WAN
- ▶ Data communication and telecommunication networks
- ▶ Indoor applications

Ordering Information

DESCRIPTION	PART NO.
Lockable IP65 Indoor/Outdoor Distribution Box	W24XXX00

Technical Specification

PRODUCT SPECIFICATION	
Height	258mm
Width	186mm
Depth	61mm
Net weight	797 grams
Packed weight	875 grams
Packaged dimensions	275mm x 197mm x 65mm
IP rating	IP65
Suitable for adapter type	SC Duplex LC Quad
Number of fibres	12
Number of ports	6
Cable entry 20mm	1
Cable exit 20mm	2
Material	ABS
Colour	RAL 7035
Operating temperature	-40°C to +50°C
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754, EN297-1
Compliant to	RoHS, Reach/SVHC

