



Part Number: 1868ENH

Category 5e Nonbonded-Pair ScTP Cable

Product Description

Cat. 5e (100MHz), 4-Pair, F/UTP Foil shielded, Work Area Patch Cable, 26 AWG stranded (7x34) bare copper conductors, Polyethylene insulation, Beldfoil® shield, AWG 26 stranded (7x34) tinned copper drainwire, LSZH jacket, RJ-45 compatible

Technical Specifications

Product Overview

Environmental Space:	Indoor
Suitable Applications:	Work area patch cable; Support current and future Category 5e applications, such as: 1000Base - T (Gigabit Ethernet), 100 Base - T, 10 Base - T, FDDI, ATM

Physical Characteristics (Overall)

Conductor

Element	AWG	Stranding	Material	No. of Pairs
Individual pair	26	7x34	BC - Bare Copper	4

Conductor Count:	8
Total Number of Pairs:	4
AWG Size:	26

Insulation

Element	Type	Material	Nominal Diameter
Individual pair	Dielectric	Polyethylene	0.95 mm

Color Chart

Number	Color
Pair 1	Black/Blue & Blue
Pair 2	Black/Orange & Orange
Pair 3	Black/Green & Green
Pair 4	Black/Brown & Brown

Outer Shield Material

Type	Material	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Position
Tape	Aluminum / Polyester	100 %	Stranded tinned copper	26 (7xAWG34)	Under foil

Note:	Aluminum facing inside in contact with drain wire
-------	---

Outer Jacket Material

Material	Color	Nominal Diameter	Diameter +/- Tolerance	Max. Diameter	Min. Wall Thickness	Nominal Wall Thickness
LSZH / FRNC	Grey (RAL 7032) and Blue (RAL 5015)	5.4 mm	0.3 mm	5.9 mm	0.4 mm	0.45 mm

Construction and Dimensions

Min Elongation at Breakof Conductors:	10 %
Min Elongation at Breakof Insulation:	100 %
Min Elongation at Breakof Jacket:	100 %
Min Tensile Strength of Jacket:	9 MPa

Electrical Characteristics

Conductor DCR

Max. Conductor DCR	Max DCR Unbalanced Between Pairs [%]	Max. DCR Unbalanced Within Pair [%]
145 Ohm/km	4 %	2 Ohm

Capacitance

Max. Capacitance Unbalance	Max. Mutual Capacitance
1,600 pF/m	56 pF/m

Impedance

Nominal Characteristic Impedance
100 Ohm

Delay

Max. Delay Skew	Min. Velocity of Propagation
40 ns/100m	60 %

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Min. TCL [dB]	Min. ELTCTL [dB]
1 MHz	3.2 dB/100m	65.3 dB	62.3 dB	62.1 dB	59.1 dB	64 dB	61 dB	20 dB	40 dB	35 dB
4 MHz	6 dB/100m	56.3 dB	53.3 dB	50.3 dB	47.3 dB	52 dB	49 dB	23 dB	34 dB	23 dB
10 MHz	9.5 dB/100m	50.3 dB	47.3 dB	40.8 dB	37.8 dB	44 dB	41 dB	25 dB	30 dB	15 dB
16 MHz	12.1 dB/100m	47.2 dB	44.2 dB	35.2 dB	32.2 dB	39.9 dB	36.9 dB	25 dB	28 dB	10.9 dB
20 MHz	13.5 dB/100m	45.8 dB	42.8 dB	32.2 dB	29.2 dB	38 dB	35 dB	25 dB	27 dB	9 dB
31.25 MHz	17.1 dB/100m	42.9 dB	39.9 dB	25.8 dB	22.8 dB	34.1 dB	31.5 dB	23.3 dB	25.1 dB	5.5 dB
62.5 MHz	24.8 dB/100m	38.4 dB	35.4 dB	13.6 dB	10.6 dB	28.1 dB	25.1 dB	20.7 dB	22 dB	
100 MHz	32 dB/100m	35.3 dB	32.3 dB	3.3 dB	0.3 dB	24 dB	21 dB	19 dB	20 dB	

High Freq Table Note: Limits below 4MHz are for information only.

Coupling Attenuation

Coupling Attenuation [dB]
Type II dB

Coupling Attenuation Class: Type II

Transfer Impedance

Frequency [MHz]	Description	Transfer Impedance
1 Mhz	Grade 2	Max.50 mOhm/m
10 Mhz		Max.100 mOhm/m
30 Mhz		Max.200 mOhm/m
100 Mhz		Max.1000 mOhm/m

Current

Max. Recommended Current [A]
1.5 A

Voltage

Voltage Rating [V]
72 V

Temperature Range

Installation Temp Range:	0°C To +50°C
Operating Temp Range:	-30°C To +60°C

Mechanical Characteristics

Bulk Cable Weight:	31 kg/km
Max Recommended Pulling Tension:	45 N
Min Bend Radius During Installation:	42 mm
Min Bend Radius During Operation:	21 mm

Standards

ISO/IEC Compliance:	ISO/IEC 11801 Ed. 2.2:2002/A2:2010/C1:2011
CENELEC Compliance:	EN 50173-1 Ed. 3:2011
Data Category:	Category 5e

ANSI Compliance:	ANSI/TIA/EIA 568-B.2-1 (2002)
------------------	-------------------------------

Flammability, LS0H, Toxicity Testing

ISO/IEC Flammability:	IEC 60332-1
Burning Load:	395 kJ/m
Amount of Halogen acc. to IEC 60754-1 & EN50267-1: Zero	

Part Number

Variants

Item #	Color
1868ENH.00B100	GRAY
1868ENH.001000	GRAY, RAL 7032
1868ENH.00500	GRAY, RAL 7032

Patent:	http://www.belden.com/p
---------	---

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be instock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.