

CSS326-24G-2S+RM

SwOS powered 24 port Gigabit Ethernet switch with two SFP+ ports, wire speed connectivity with several new switching features.

The device is powered by a Marvell DX switch chip. The device is running an operating system designed specifically for MikroTik switch products - SwOS. SwOS is configurable from your web browser. It gives you all the basic functionality for a managed switch, plus more: allows to manage port-to-port forwarding, apply MAC filter, configure VLANs, mirror traffic, apply bandwidth limitation and even adjust some MAC and IP header fields. SFP cage supports both 1.25 Gb SFP and 10 Gb SFP+ modules.

Specifications

| | |
|----------------------------|---------------------------------|
| Product code | CSS326-24G-2S+RM |
| Switch chip model | 98DX3216A1 |
| Storage type | Flash |
| Storage size | 2 MB |
| 10/100/1000 Ethernet ports | 24 |
| SFP+ cages | 2 |
| Operating system | SwOS |
| Supported input voltage | 10 - 30 V (jack or passive PoE) |
| Dimensions | 440 x 144 x 44 mm |
| Operating temperature | -40°C .. +70°C tested |
| Max power consumption | 19 W |

Features

- Non-blocking Layer 2 switching capacity
- 16K host table
- IEEE 802.1Q VLAN
- Supports up to 4K simultaneous VLANs
- Port isolation
- Port security
- Broadcast storm control
- Port mirroring of ingress/egress traffic
- Rapid Spanning Tree Protocol
- Access Control List
- MikroTik neighbor discovery
- SNMP v1
- Web-based GUI

Included



24 V 1.2 A power adapter



Rack ears

