



NOTE:

- 1.100% OPEN SHORT, MISS WIRE TEST
2.Fluke test
Test limit:ISO 11801 CHANNEL CLASS EA
3.PRINT WORD:CAT.6A U/FTP FLAT CABLE 500MHz
CONFORM TO ISO/IEC 11801 & EN50173-1 & ANSI/TIA-568-C.2
4.ROHS2.0 AND REACH COMPLIANT

MATERIAL LIST

③	OVER MOLD	PVC Colour black	2	
②	CONNECTOR	RJ45 8P8C shielded Plug, Pin Gold Plated, Transparent red	2	
①	CABLE	(32AWG BC*1P+AL-FOIL)*2+(32AWG BC*1P+AL-FOIL+E)*2 JACKET:PVC/black OD:T=1.75±0.2mm W=6.6±0.2MM	1	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK

ITEM	LENGTH
21.99.0830	500±30mm
21.99.0831	1000±30mm
21.99.0834	1500±50mm
21.99.0832	2000±50mm
21.99.0833	3000±70mm
21.99.0835	5000±70mm

					DESC.	VALUE CAT 6A U/FTP FLAT PATCH CABLE, BLACK
		NEW	2016-06-01	A		
BY	CHK	REVISION RECORD MODIFICATION	DATE	REV.		