



REV	DATE	BY	CHK	APR	DESCRIPTION



PANDUIT P/N	WEIGHT
P12B34M	1.0kg

NOTES:

1. IDENTIFICATION:

UNIT TYPE:	BASIC
ORIENTATION:	HORIZONTAL, 1U
OUTLET QTY&TYPE:	(12) C13
BREAKER QTY&TYPE:	N/A
INPUT VOLTAGE:	100-120V
INPUT CURRENT:	16A
INPUT PHASE:	SINGLE-PHASE
RATED POWER:	3.7kVA
INPUT PLUG:	IEC 60309 2P+E 6H 16A
INPUT CORD LENGTH:	3m [10']

2. ACCESSORIES:

POCKET GUIDE  
QTY: (4) M6 X 12 PAN HEAD MACHINE SCREWS  
QTY: (4) M6 CAGED NUT

### 3. RoHS COMPLIANT

4. VISIT PANDUIT'S ON-LINE CATALOG AT [WWW.PANDUIT.COM](http://WWW.PANDUIT.COM) FOR ADDITIONAL PRODUCT INFORMATION CONTAINED IN THE SPECIFICATION SHEET AS WELL AS A CURRENT LIST OF PRODUCTS APPLICABLE FOR USE WITH THIS PART
5. MAXIMUM ALLOWABLE INPUT POWER = 3.7 kW
6. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE, AND LOCAL CODES

WE ASK THAT YOU CHECK FULLY THE DIMENSIONS, NOTES, AND SIGN THE CLIENT SIGNATURE BOX. THE JOB WILL NOT PROGRESS WITHOUT SIGNED APPROVAL. PLEASE DO NOT DELAY IN RETURNING PROOF AS IT WILL AFFECT DELIVERY				SIGN  DATE  PRINT	
TITLE  <div style="text-align: center;">           BASIC SERIES PDU            P12B34M            CUSTOMER DRAWING         </div>					
ITEM REVISION NAME					
DATASHEET FILE NAME					
UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCE ARE: mm [IN]				MATERIAL/COLOR:  <div style="text-align: center; font-size: 2em;">N/A</div>	
<div style="display: flex; align-items: center;">  <div style="margin-left: 10px;">           THIRD ANGLE PROJECTION         </div> </div>				DRAWING NUMBER:  <div style="text-align: center; font-size: 2em;">P12B34M_DC</div>	
DRAWN BY JIANG		DATE 05/24/2017		SCALE B	
CHK SEAN		SCALE NONE		SHT 1 OF 1	