



www.grandstream.com



#### OFFICE LOCATIONS

##### NORTH AMERICA

**Corporate Headquarters**  
126 Brookline Ave, 3rd Floor  
Boston, MA 02215  
Voice: +1 617-566-9300  
Fax: +1 617-249-1987

**California**  
1208 John Reed Court  
City of Industry, CA 91745  
Voice: +1 626-638-9172  
Fax: +1 617-249-1987

**Dallas**  
2301 W. Plano Pkwy, Suite 208  
Plano, TX 75075  
Voice: +1 469-241-0100  
Fax: +1 617-249-1987

##### ASIA

Shenzhen, China  
Hangzhou, China  
Kuala Lumpur, Malaysia

##### EUROPE, MIDDLE EAST & AFRICA

Casablanca, Morocco

##### LATIN AMERICA


Valencia, Venezuela

## SIP Intercom

### GSC3510

#### SIP Intercom Speaker/Microphone


High-fidelity 8W speaker, 3 directional mics, advanced acoustic echo cancellation, Bluetooth, dual-band WiFi, 1x 10/100 Mbps ports, PoE/PoE+, 2-pin multi-purpose input, Full-band and wide-band codec support



### GSC3505

#### 1-Way Public Address SIP Speaker

High-fidelity 8W speaker, Bluetooth, dual-band WiFi, 1x 10/100 Mbps ports, PoE/PoE+, Full-band and wide-band codec support



## WiFi Access Points & Routers

### GWN7630



4x4:4 MIMO, 200+ clients, 2.33 GBps, 175 meter range

### GWN7610




3x3:3 MIMO, 250+ clients, 1.75 GBps, 175 meter range

### GWN7600



2x2:2 MIMO, 450+ clients, 1.27 GBps, 165 meter range

### GWN7600LR



Weatherproof casing, 2x2:2 MIMO, 450+ clients, 1.27 GBps, 300 meter range

### GWN7000

#### Multi-WAN Gigabit Router

7 Gigabit ports (2 WAN, 5 LAN), Hardware accelerated VPNs, Embedded controller, 10 GBps, load balancing, & failover, firewall



## Extension Module

### GXP2200 EXT

#### Extension Module for IP Phones

20 dual-colored extension keys, 2 arrow keys, up to 40 contacts stored per extension module, connect up to 4 extension modules for up to 160 contacts



## ATAs and Gateways

### HT812/814/818

#### Analog Telephone Adapters



2/4/8 FXS ports, 2 SIP profiles, 2 Gigabit network ports with NAT router, auto-provisioning

### HT813

#### Analog Telephone Adapter



1 FXS port, 1 FXO port with lifeline support, 2 10/100Mbps ports, 2 SIP profiles,

### HT801 / 802

#### Analog Telephone Adapter



1/2 FXS ports, 1 10/100Mbps port, 1/2 SIP profiles, auto provisioning

### GXW4500 Series

#### Digital VoIP Gateways

1/2/4 E1/T1/J1 spans, supports 30,60, or 120 concurrent calls, Gigabit network port, TLS and SRTP security encryption



### GXW4200 Series

#### High Density FXS Gateways

16/24/32/48 FXS ports, 1 Gigabit network port, 4 SIP server profiles per system, independent SIP account per port, 132x48 backlit display



### GXW4100 Series

#### Mid-Density FXO/FXS Gateways

4/8 FXO ports, 2 SIP profiles, integrated NAT router



## IP Surveillance

### GXV3610\_HD /\_FHD

#### IP Camera



3.6mm lens, Infrared, IP66-certified weather-proof, PoE

### GXV3674\_FHD

#### IP Camera



Variable-focal lens (2.8mm-12mm), IP66-certified weatherproof, Infrared, PoE

### GXV3500

#### Video Encoder/Decoder/PAS



1-channel IP video encoder/decoder/public address system device, H.264, PoE



# Unified Communications Solutions

*For Small, Medium and Large Businesses*



## Carrier Grade IP Phones

### GRP2612 / 2612P / 2612W



2 SIP accounts, 2.4" LCD, 16 VPKs, cloud provisioning & management (GDMS), carrier-grade security, HD voice, swappable faceplate, 2x 10/100 MBps ports, PoE (GRP2612P), WiFi (GRP2612W)

### GRP2613



3 SIP accounts, 2.8" LCD, 24 VPKs, cloud provisioning & management (GDMS), carrier-grade security, HD voice, swappable faceplate, PoE, 2x 10/100 MBps ports, PoE

### GRP2614



4 SIP accounts, Dual LCDs (2.8" + 2.4") 40 VPKs, cloud provisioning & management (GDMS), carrier-grade security, WiFi, Bluetooth, swappable faceplate, 2x Gigabit ports, PoE

### GRP2615



16 SIP accounts, 4.3" LCD, 40 VPKs, cloud provisioning & management (GDMS), carrier-grade security, WiFi, Bluetooth, swappable faceplate, 2x Gigabit ports, PoE

## IP Video Phones for Android

### GXV3380



16 lines, 16 SIP accounts, dual Gigabit ports, PoE, 8" touch screen, WiFi, Bluetooth, Android 7.X, 2 MP camera, 1080p HD video output

### GXV3370



16 lines, 16 SIP accounts, dual Gigabit ports, PoE, 7" touch screen, WiFi, Bluetooth, Android 7.0, 1 MP camera, 720p HD video output

### GXV3240



6 lines, 6 SIP accounts, dual Gigabit ports, PoE, 4.3" touch screen, WiFi, Bluetooth, Android 4.2, 1 MP camera, 720p HD video output

## High-End IP Phones

### GXP2170



12 lines, 6 SIP accounts, dual Gigabit ports, PoE, 48 VPKs, Bluetooth

### GXP2160



6 lines, 6 SIP accounts, dual Gigabit ports, PoE, 24 BLF/speed dial keys, Bluetooth

### GXP2140



4 lines, 4 SIP accounts, dual Gigabit ports, PoE, Bluetooth

### GXP2135



8 lines, 4 SIP accounts, dual Gigabit ports, PoE, 32 VPKs, Bluetooth

### GXP2130



3 lines, 3 SIP accounts, dual Gigabit ports PoE, 8 BLF/speed dial keys, Bluetooth

## Mid-Range IP Phones

### GXP1760 / 1760W



6 lines, 3 SIP accounts, PoE, 24 digital BLF/speed dial keys, WiFi (GXP1760W)

### GXP1780 / 1782



8 lines, 4 SIP accounts, dual Gigabit ports (1782), PoE, 32 digital BLF/speed dial keys

## Basic IP Phones

### GXP1630



3 lines/SIP accounts, dual Gigabit ports, PoE, 8 BLF/speed dial keys

### GXP1628



2 lines/SIP accounts, dual Gigabit ports, PoE, 8 BLF/speed dial keys

### GXP1620/1625



2 lines/SIP accounts, dual 10/100Mbps ports, PoE (GXP1625)

### GXP1610/1615



2 lines, 1 SIP account, dual 10/100Mbps ports, PoE (GXP1615)

## Mobility IP Phones

### WP820

#### Enterprise Portable WiFi Phone



2 lines, 2 SIP accounts, dual-band WiFi, Bluetooth, HD voice, rechargeable battery, 7.5 hour talk time, push-to-talk

### DP752/DP750

#### DECT Base Stations



High-end and mid-tier DECT base stations support any current DP device, up to 400m range outdoors and 50m range indoors

### DP760

#### Wideband DECT repeater



Pairs with DP752/DP750 to extend range an additional 300m outdoors and 50m indoors

### DP730/DP722/DP720

#### DECT Cordless HD IP Phones



10 line / 10 SIP account DECT handsets, HD voice, color-screens, over-the-air software/firmware updates, push-to-talk

## IP PBXs

### UCM6200 Series

#### IP PBX



UCM6202/6204: Up to 500 users, 50/75 concurrent calls, 2/4 FXO ports, 2 FXS ports, auto-provisioning, CDR

UCM6208: Up to 800 users, 100 concurrent calls, 8 FXO ports, 2 FXS ports, auto provisioning, CDR

### UCM6510

#### IP PBX



Up to 2000 users, 200 concurrent calls, E1/T1/J1, 2 FXS ports, auto provisioning, CDR, pair 2 UCM6510s with an HA100 for a high-availability solution

### HA100

#### High Availability Controller for the UCM6510



**Interfaces Back Panel:**  
2 FXS A, 2 FXS B, 2 FXO A, 2 FXO B, 1 T1/E1 A, 1 T1/E1 B, 2 LAN/ 2 WAN

**Interfaces Front Panel:**  
2 FXS ports, 2 FXO ports, 1 T1/E1, 1 LAN/1 WAN, 1 RS-485 for Primary UCM6510, 1 RS-485 for Secondary UCM6510

## Video & Audio Conferencing

### GVC3200/3202

#### Video Conferencing System



Supports Android, SIP and H.323 platforms, built-in MCU for 9/3-way video, 3/2 HDMI outputs, screen-sharing, Bluetooth, WiFi (GVC3200 only)

### GVC3210

#### Video Conferencing Endpoint



Supports Android, SIP and H.323 platforms, 4k video resolution, 2 HDMI outputs, Miracast screen-sharing, Bluetooth, WiFi

### IPVT10

#### Enterprise Video Conferencing Server



On-premise collaboration server, up to 300 participants, 10 simultaneous sessions, 120 video feeds per session, built-in recording & reports, advanced meeting control & scheduling, support for PC/ Mac/mobile & SIP devices/PSTN trunk

### GAC2500

#### HD IP Conference Phone



Android based, 6 lines, 4.3" color screen, 7-way conference bridge, Gigabit LAN port, PoE, integrated WiFi & Bluetooth

## Facility Access Systems

### GDS3710

#### HD IP Video Door System



Built-in hemispheric camera for 180° view 1080p video resolution, microphone and speaker for intercom functionality, Weatherproof/vandal-resistant metal casing, RFID chip reader, free management system, PoE

### GDS3705

#### IP Audio Door System



Dual microphones and speaker for intercom functionality, Weatherproof/vandal-resistant metal casing, RFID chip reader, free management system, PoE