

## Product Information

Vertical power distribution unit single phase 24xNF C61-314 (PL,FR standard), plug IEC 60309, LED control light

Power Distribution Units (PDUs) are designed for basic power distribution, designed for telecommunications cabinets.

The devices are intended for vertical installations. The housing is made of black aluminum.




M6 screws with nuts in a box with washers attached to each PDU.




## Standards

EN 60950-1, EN 60669-1, EN 60669-2-1

## Features

Index no.	11341730.24-1
Power plug	IEC 60309 16A/250V
Cable	H05VV-F 3 x 2.5 mm <sup>2</sup> , 3.0 m, black
Sockets	24 x NF C61-314 16A/250V
Additional components	LED control light
Maximum unit load	16A
Unit rated power	3680W
Dimensions (L x W x D) [mm]	1227 x 44 x 68
Net weight [kg]	2.7
Gross weight [kg]	3.2
Housing	0U, black aluminum
Fixed brackets type 44	
Brackets for BKT 4DC cabinets (set) Index: 111SA200011.3	
Brackets for BKT SRS/SSRS cabinets (must be ordered separately) Index: 111SA200018.3	
Power plug view	

SOCKETS 16A/250V  NF C61-314	RATED POWER  <b>3.7 kW</b>
CABLE LENGTH  <b>3.0 m</b>	WARRANTY  <b>2 YEARS</b>