


NOTE:

- 1.ELECTRICAL TEST:100% OPEN SHORT, MISS WIRE TEST
- 2.FLUKE Channel TEST:  
TEST LIMIT:ISO11801 Channel Class EA
- 3.Working temperature:-10℃~+60℃  
Storage temperature:-20℃~+75℃
- 4.RoHS2.0 AND REACH compliant
- 5.Spray WORD:CAT6A U/FTP 4x2x32AWG/7 Ultraflex LSZH-TPE  
ISO11801 & EN50173 & ANSI/TIA568C.2
- 6.Minimum of the bending radius is 15mm(Suitable for all meters)

## PIN OUT



CN1 (568B)                      CN2 (568B)

- 
- Diagram illustrating the eight propagation modes of a four-core optical fiber. The modes are arranged in four pairs, each corresponding to a core color:
- White-Orange (Modes 1 and 2):** The electric field is concentrated in the white and orange cores.
  - White-Green (Modes 3 and 6):** The electric field is concentrated in the white and green cores.
  - Blue (Modes 4 and 5):** The electric field is concentrated in the blue core.
  - White-Brown (Modes 7 and 8):** The electric field is concentrated in the white and brown cores.
- The diagram shows the spatial distribution of the electric field for each mode, with the cores labeled "SHELL" and "DRAIN".

## MATERIAL LIST

③	OVER MOLD	75A PVC WHITE(RAL9003)	2	
②	PLUG	RJ45 8P8C Shielded Plug, PIN GOLD PLATED 3u", THE SHELL PLATED NICKEL, COLOUR:TRANSPARENT	2	
①	CABLE	CAT. 6A U/FTP CABLE (32AWG BC*1P+AL-FOIL)*4+DRAIN JACKET:ULTRAFLEX LSZH-TPE/WHITE (RAL9003), OD:3.6±0.2MM	1	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK
		NEW		2022-07-01
BY	CHK	REVISION RECORD MODIFICATIONS		DATE

Item NO.	Length (mm)
21. 44. 1698	$150 \pm 10$
21. 44. 1699	$300 \pm 10$
21. 44. 1700	$500 \pm 20$
21. 44. 1701	$1000 \pm 20$
21. 44. 1704	$1500 \pm 30$
21. 44. 1702	$2000 \pm 30$
21. 44. 1703	$3000 \pm 50$
21. 44. 1705	$5000 \pm 100$

DESC.	ROLINE GREEN Cat.6A U/FTP Patch cord 10G Slim Type Ultraflex LSZH-TPE, white