

# TV / SAT, Coaxial - 75 Ohm (Class A)

**Číslo zboží:** KH 21-500 DR ,BR  
**Označení:** Cable on Spool  
**Název:** TV / SAT, Coaxial - 75 Ohm (Class A)  
**Popis:** 500 m, white, spool packing

## KH 21 D

inner conductor ř mm, material	1,1 Cu
insulation ř mm, material	4,8 foamed PE
1. screening, foil	Al-foil double faced
2. screening braid, material	128 x 0,12 Al
jacketed ř mm, material/colour	6,8 PVC/white
attenuation at (20 řC in dB/100m):	
100 MHz	5,1 dB
200 MHz	6,9 dB
300 MHz	8,8 dB
500 MHz	12,2 dB
800 MHz	15,6 dB
1000 MHz	17,8 dB
1350 MHz	21,7 dB
1750 MHz	24,4 dB
2050 MHz	27,8 dB
impedance	75 $\Omega$
screening immunity	> 95 dB
velocity factor v/c	0,80
min. bending radius mm	70
coil packing	-
carton box packing	-
spool packing	500 m

printing on cable jacket: DOPPELT GESCHIRMT FÜR DIGITALE UND  
SAT-ANLAGEN  
ZZF G 686 561 B CE digital " meter print 500 m -> 1 m" Class A

Designed by ABE & JRH